

TEST EQUIPMENT



AKRON BRASS Apparatus Flow Test Kit

ARK-FK-25, ARK-FK-25-2

Includes your choice of four (4) out of the fifteen (15) tips offered, whichever suits your testing requirements. Errors associated with hand held pitot units are virtually eliminated. Pitot arm is held firmly in the correct position at all times for accurate readings. The Apparatus Flow Test Kit flows between 151-1851 GPM @ 10-140 PSI range, depending on tip size selected and water pressure.



AKRON BRASS Hydrant Flow Test Kit

ARK-HK-25

Includes a 2-1/2" barrel with pitot tube properly positioned in the waterway, 3-1/2" gauge, and Water Diffuser Assembly. Reduces property damage such as torn up yards and washed out driveways. The 2-1/2" barrel easily measures flows between 608-1851 GPM @10-140 PSI range. Large heavy duty, black case is optional.



AKRON BRASS Cap Gauge

ARK-CG-15

Is designed for determining the static pressure of water in fire hydrants, fire hoses, and/or fire pumps. The Cap Gauge is a two part, full swivel cap with rocker lugs. A 3-1/2" liquid filled, 0-160 PSI gauge is standard. Gauges with higher or lower pressure ranges are available upon request.



AKRON BRASS Hand Held Pitot

ARK-HH-PITOT

Is designed to measure straight tip or hydrant flow pressures to determine the actual PSI. The PSI reading may then be converted to GPM by referring to the provided chart. The all brass pitot arm is heavy duty and virtually impossible to break, eliminating the problems associated with plastic pitots. Measures flows between 151-1851 GPM @ 10-140 PSI range.



ELKHART Line Gauge

LINE GAUGE

- Fully guarded, liquid-filled luminescent gauge
- Hard anodized Elk-O-Lite® body
- 228A – 1.5" 0-200 gauge with 1.5" free swivel inlet, 1.5" outlet, and 6" length
- 228A – 2.5" 0-200 gauge with 2.5" free swivel inlet, 2.5" outlet, color-coded zones, and 6.9" length



ELKHART EB-500 Portable Flowmeter

ELK-EB-500

- Digital 0-500 gpm read-out display
- Flowmeter and flowtube-mounted paddlewheel flow sensor
- Low and high flow warnings
- Weather-tight PVC Pelican case includes: flowmeter, power switch, low battery indicator, rechargeable battery, AC charger/power supply, cable connections and cord storage space
- Weight: 17 lbs.
- Finish is hard anodized
- 2.5" flow tube (NST threads)



FLAMEFIGHTER HT100 Hose Tester

FLA-HT100

Our HT100 Hose Tester is easy to use, comes standard with four outlets, stainless steel ball valves. Pumps 3 gallons a minute @ 600 PSI. Capable of testing up to 6" diameter hose, and up to 300 ft per discharge.

The wheeled cart fits through a standard 36" door way

Also included is a built-in pressure washer with 50 ft. of 3/8" non-marking hose, quick release heavy duty wand & handle, a quick connect injector and metering valve for adding cleaning agents to water supply and a stainless steel nozzle with stream straightener.

Pressure washer unit can be removed from wheeled cart for ease of use.

HT100 – Hose Tester with Pressure Washer (shown)

HT156 – Hose Tester with Pressure Washer (6 Outlets)

HT50 – Hose Tester without Pressure Washer

HT56 – Hose Tester without Pressure Washer (6 Outlets)

Features

- Pressure Washer System included
- Complies with NFPA standards
- 1-1/2" connection standard
- Built-in Tool Tray
- Stainless Steel Ball Valves
- 3 Gallons a Minute @ 600 PSI
- Capable of Testing up to 6" dia. Hose
- 300 ft. per Discharge
- Heavy Duty Wand & Handle
- 50 ft of 3/8" Non-Marking Hose
- Quick Connect Injector and Metering Valve for Adding Cleaning Agents
- Wheeled Cart
- Fits Standard 36" Door Way